

3系列选型规则/Group 3 Ordering Code Rules

B	H	P	3	A0	D	20	C0	E0	省略/omit	省略/omit	省略/omit
博顿 Boden	材质 Material	功能 Function	系列 Group	前盖 Front cover	旋向 Rotation	排量 Displacement	轴伸 Shaft	泵体油口 Ports	特殊结构 Special structure	可选项 Options	其他 Other
A	前、后盖材料为铝合金 Front and end cover material aluminum	P 泵 Pump M 马达 Motor	3 3系列 Group 3		D 顺时针转 Clockwise S 逆时针转 Counter clockwise R 可正反转 Reversible	20 22 26 33 39 46 50 52 55 63 71					特殊设计 special designing
H	前、后盖材料为铸铁，压力比铝盖高 30bar。 Front and end cover material cast iron, pressure 30 bar higher than aluminum covers									可选项 Options 省略-温度范围在-10℃~+80℃, 进油口最高绝对压力为3bar。 Omit-Range between -10℃ and +80℃, inlet pressure up to max. 3 bar absolute. V 适用于高温介质, 温度范围在-10℃~+120℃。 Version suitable for fluid at hi-temperatures, range between -10℃ and +120℃. H 适用于低温介质, 温度范围在-40℃~+80℃。 Version suitable for fluid at low-temperatures, range between -40℃ and +80℃. N 适用于进油口最大绝对压力3~10bar。 Version suitable for inlet pressure up to max. 3 and 10 bar absolute. 如需其它特殊选项请联系本公司工程师 For other special options, please contact our engineers.	

前盖 Front cover		轴伸 Shaft		泵体油口 Ports		特殊结构 Special structure	
A0	菱形前盖 (止口 $\phi 101.6$) Diamond front cover (centering $\phi 101.6\text{mm}$)	T0	锥形键槽轴 1:8 Taper shaft 1:8	E	矩形法兰 Rectangular flange		省略-默认普通 omit-regular
A1	菱形前盖 (止口 $\phi 100$) Diamond front cover (centering $\phi 100\text{mm}$)	T1	锥形键槽轴 1:5 Taper shaft 1:5	F	矩形法兰 Rectangular flange		
B0	方形前盖 (止口 $\phi 90$) Square front cover (centering $\phi 90\text{mm}$)	C0	平键轴 $\phi 25$ straight keyed $\phi 25$	F	矩形法兰 Split flange	Q	后盖带泄油口 Back cover with oil drain
B1	方形前盖 (止口 $\phi 50.8$) Square front cover (centering $\phi 50.8\text{mm}$)	C2	平键轴 $\phi 22.22$ straight keyed $\phi 22.22$	Z	公制螺纹 (M) Metric thread		
B2	方形前盖 (止口 $\phi 105$) Square front cover (centering $\phi 105\text{mm}$)	C3	平键轴 $\phi 25.4$ straight keyed $\phi 25.4$	L	英制管螺纹 (G) Gas thread		
		H0	矩形花键轴 Rectangle spline shaft $\square 6-25 \times 20.1 \times 6$	U	美制管螺纹 (UNF-2B) UNF thread		
		H2	矩形花键轴 Rectangle spline shaft $\square 6-25 \times 21 \times 5$	R	英制锥螺纹 (PT) PT thread		
		S0	SAE花键轴 SAE spline shaft DP16/32-30°-13T	X	泵体无油口 Body without ports		
		S1	SAE花键轴 SAE spline shaft DP16/32-30°-15T				