

1.2系列选型规则/Group 1.2 Ordering Code Rules

B	A	P	1.2B	Q5	D	0.8	G1	L3	省略/omit	省略/omit	省略/omit
博顿 Boden	材质 Material	功能 Function	系列 Group	前盖 Front cover	旋向 Rotation	排量 Displacement	轴伸 Shaft	泵体油口 Ports	特殊结构 Special structure	可选项 Options	其他 Other
A	前、后盖材料为铝合金 Front and end cover material aluminum	P 泵 Pump	1.2B 1.2B系列 Group 1.2B 1.2F 1.2F系列 Group 1.2F		D 顺时针转 Clockwise S 逆时针转 Counter clockwise R 可正反转 Reversible	0.8 1.2 1.7 2.5 3.2 4.3 5 6 6.5 7.8 8.5 10 12					特殊设计 special designing
H	前、后盖材料为铸铁，压力比铝盖高 30bar。 Front and end cover material cast iron, pressure 30 bar higher than aluminum covers								可选项 Options 省略-温度范围在-10℃~+80℃, 进油口最高绝对压力为3bar。 Omit-Range between -10℃ and +80℃, inlet pressure up to max. 3 bar absolute. V 适用于高温介质, 温度范围在-10℃~+120℃。 Version suitable for fluid at hi-temperatures, range between -10℃ and +120℃. H 适用于低温介质, 温度范围在-40℃~+80℃。 Version suitable for fluid at low-temperatures, range between -40℃ and +80℃. N 适用于进油口最大绝对压力3~10bar。 Version suitable for inlet pressure up to max. 3 and 10 bar absolute. 如需其它特殊选项请联系本公司工程师 For other special options, please contact our engineers.		

前盖 Front cover	轴伸 Shaft	泵体油口 Ports	特殊结构 Special structure
1.2B系列/Group 1.2B		1.2B系列/Group 1.2B	

Q5 方形前盖 (止口 φ45.2) Square front cover (centering φ45.2mm)	G1 扁平轴 Tang shaft G8 扁平轴 Tang shaft	Z_ 公制螺纹 (M) Metric thread L_ 英制管螺纹 (G) Gas thread U_ 美制管螺纹 (UNF-2B) UNF thread R_ 英制锥螺纹 (PT) PT thread	省略-默认普通 omit-regular
详见 51 页 See page 51 for details	详见 51 页 See page 51 for details		

1.2F系列/Group 1.2F		1.2F系列/Group 1.2F	
--------------------------	--	--------------------------	--

Q0 方形前盖 (止口 φ32) Square front cover (centering φ32mm)	G0 扁平轴 Tang shaft G4 扁平轴 Tang shaft	X 泵体无油口 Body without ports	省略-默认普通 omit-regular
Q2 方形前盖 (止口 φ32) Square front cover (centering φ32mm)			J_ 后盖带进油口 Back cover with inlet Q_ 后盖带泄油口 Back cover with oil drain