

# 2系列选型规则/Group 2 Ordering Code Rules

B	A	P	2	B0	D	3	T0	E0	省略/omit	省略/omit	省略/omit
博顿 Boden	材质 Material	功能 Function	系列 Group	前盖 Front cover	旋向 Rotation	排量 Displacement	轴伸 Shaft	泵体油口 Ports	特殊结构 Special structure	可选项 Options	其他 Other
A	前、后盖材料为铝合金 Front and end cover material aluminum	P 泵 Pump M 马达 Motor	2 2系列 Group 2		D 顺时针转 Clockwise S 逆时针转 Counter clockwise R 可正反转 Reversible	3 4 6 8 10 12 14 16 18 20 22 25 28 30					特殊设计 special designing
H	前、后盖材料为铸铁，压力比铝盖高 30bar。 Front and end cover material cast iron, pressure 30 bar higher than aluminum covers								可选项 Options 省略-温度范围在-10℃~+80℃, 进油口最高绝对压力为3bar。 Omit-Range between -10℃ and +80℃, inlet pressure up to max. 3 bar absolute. V 适用于高温介质, 温度范围在-10℃~+120℃。 Version suitable for fluid at hi-temperatures, range between -10℃ and +120℃. H 适用于低温介质, 温度范围在-40℃~+80℃。 Version suitable for fluid at low-temperatures, range between -40℃ and +80℃. N 适用于进油口最大绝对压力3~10bar。 Version suitable for inlet pressure up to max. 3 and 10 bar absolute. 如需其它特殊选项请联系本公司工程师 For other special options, please contact our engineers.		

前盖 Front cover		轴伸 Shaft		泵体油口 Ports		特殊结构 Special structure	
A0	菱形前盖 (止口 φ82.55) Diamond front cover (centering φ82.55mm)	T0	锥形键槽轴 1:8 Taper shaft 1:8	E	矩形法兰 Rectangular flange		省略-默认普通 omit-regular
B0	方形前盖 (止口 φ36.5) Square front cover (centering φ36.5mm)	T1	锥形键槽轴 1:5 Taper shaft 1:5	F	矩形法兰 Rectangular flange	Q	后盖带泄油口 Back cover with oil drain
B1	方形前盖 (止口 φ38) Square front cover (centering φ38mm)	C0	平键轴 straight keyed	F	矩形法兰 Split flange		后盖带进油出口 Back cover with inlet and outlet
B2	方形前盖 (止口 φ80) Square front cover (centering φ80mm)	G0	扁平轴 Tang shaft	Z	公制螺纹 (M) Metric thread	DF0	后盖带单向阀 Back cover with one-way valve
Q0	方形前盖 (止口 φ50) Square front cover (centering φ50mm)	G1	扁平轴 Tang shaft	L	英制管螺纹 (G) Gas thread	YF0	后盖带溢流阀 Back cover with relief valve
Q2	方形前盖 (止口 φ52), O-RING Square front cover (centering φ52mm), O-RING	H0	矩形花键轴 Rectangle spline shaft 4-15x11.4x4	U	美制管螺纹 (UNF-2B) UNF thread	HFA	后盖带恒流阀 Back cover with constant flow valve
		S0	SAE花键轴 SAE spline shaft DP16/32-30°-9T	R	英制锥螺纹 (PT) PT thread		
		S1	SAE花键轴 SAE spline shaft DP16/32-30°-11T	N	美制锥螺纹 (NPT) NPT thread		
		S8	SAE花键轴 SAE spline shaft DP16/32-30°-10T	X	泵体无油口 Body without ports		
详见 99 页 See page 99 for details		详见 100 页 See page 100 for details		详见 101-102 页 See page 101-102 for details		详见 103 页 See page 103 for details	